



**A STUDY OF UNBALANCED TRANSPORTATION PROBLEM  
AND USE OF OBJECT ORIENTED PROGRAMMING**

**R. Palaniyappa\*<sup>1</sup> and V. Vinoba<sup>2</sup>**

<sup>1</sup>*Department of Mathematics, IRT Polytechnic College, Chromepet, Chennai – 44, India.*

<sup>2</sup>*Department of Mathematics, K. N. G. C. (W), Thanjavur – 7, India.*

*(Received on: 15-04-14; Revised & Accepted on: 26-04-14)*

**ABSTRACT**

*In this paper, the south east corner [SEM] procedure is successfully coded and tested via many randomly generated problem instances. Based on the results we can conclude that the correctness of the newly coded SEM is promising as compared with the previously coded one.*

*Keywords: Transportation problem, LPP, optimal solution, south east corner rule, object oriented programming.*

**1. INTRODUCTION**

The term ‘OR’ was coined in 1940 by M. C. Closky & T.ref then in a small town of Bawdsey in England. It is a science that came into existence in a military content. During World War II, the military management of UK called an Scientists from various disciplines & organized them into teams to assist it in solving strategic & tactical problems relating to air & land defence of the country.

The transportation problem is a special class of LPP that deals with shipping a product from multiple origins to multiple destinations. The objective of the transportation problem is to find a feasible way of transporting the shipments to meet demand of each destination that minimizes the total transportation cost while satisfying the supply & demand constraints. The two basic steps of the transportation method are

**Step - 1:** Determine the initial basic feasible solution

**Step - 2:** Obtain the optimal solution using the solution obtained from step 1.

In this paper the corrected coding of SEM in C++ is implemented. Then its correctness is verified via many randomly generated instances. The remainder of this paper is organized as follows:

Section II deals with the mathematical formulation of the transportation problem. In section III SEM is summarized. In section IV potential significance of the new object oriented program of VAM is illustrated with a numerical example.

Finally, conclusion by highlighting the limitations and future research scope on the topic is made in section V.

**2. MATHEMATICAL FORMULATION OF THE TRANSPORTATION PROBLEM**

**A.** In developing the LP model of the transportation problem the following notations are used

$a_i$  - Amounts to be shipped from shipping origin  $i$  ( $a_i \geq 0$ ).

$b_j$  - Amounts to be received at destination  $j$  ( $b_j \geq 0$ ).

$c_{ij}$  - Shipping cost per unit from origin  $i$  to destination  $j$  ( $c_{ij} \geq 0$ ).

$x_{ij}$  - Amounts to be shipped from origin  $i$  to destination  $j$  to minimize the total cost ( $x_{ij} \geq 0$ ).

We assumed that the total amount shipped is equal to the total amount received, that is,

$$\sum_{i=1}^m a_i \geq \sum_{i=1}^m b_j$$

**\*Corresponding author: R. Palaniyappa\*<sup>1</sup> E-mail: [sivaram2003@gmail.com](mailto:sivaram2003@gmail.com)**

## B. Transportation problem

$$\text{Min } \sum_{i=1}^m \sum_{j=1}^n c_{ij} x_{ij}$$

Subject to  $\sum_{j=1}^n x_{ij} \leq a_i, i = 1, 2, \dots, m$

$\sum_{i=1}^m x_{ij} \leq b_j, j = 1, 2, \dots, n$ , where  $x_{ij} \geq 0 \forall i, j$ .

**Feasible solution:** A set of non negative values  $x_{ij}, i = 1, 2, \dots, n$  and  $j = 1, 2, \dots, m$  that satisfies the constraints is called a feasible solution to the transportation problem .

**Optimal solution:** A feasible solution is said to be optimal if it minimizes the total transportation cost.

**Non degenerate basic feasible solution:** A basic feasible solution to a  $(m \times n)$  transportation problem that contains exactly  $m + n - 1$  allocations in independent positions.

**Degenerate basic feasible solution:** A basic feasible solution that contains less than  $m + n - 1$  non negative allocation.

**Balanced and Unbalanced Transportation problem:** A Transportation problem is said to be balanced if the total supply from all sources equals the total demand in the destinations and is called unbalanced otherwise.

Thus, for a balanced problem,  $\sum_{i=1}^m a_i = \sum_{j=1}^n b_j$  and for unbalanced problem,  $\sum_{i=1}^m a_i \neq \sum_{j=1}^n b_j$ .

## 3. SOUTH EAST CORNER RULE

The steps involved in VAM in producing the initial feasible solution are described below:

This method starts at the south east corner cell (route) of the table variable ( $x_{43}$ ).

**Step - 1:** Construct the transportation table for the given TPP.

**Step - 2:** Allocate as much as possible to the selected cell and adjust the associated amounts of supply and demand by subtracting the allocated amount.

**Step - 3:** Cross out the row or column with zero supply or demand to indicate that no further assignments can be made in that row or column. If both a row and column net to zero simultaneously, cross out one only and leave a zero supply (demand in the uncrossed out row - column).

**Step 4:** If exactly one row or column is left uncrossed out, stop. Otherwise, move to the cell to the right if a column has just been crossed out. Go to step 2 [8].

## 4. OBJECT ORIENTED PROGRAM CODE FOR SOUTH EAST CORNER METHOD FOR INITIAL BASIC FEASIBLE SOLUTION

\*\*\*\*\*

### SOUTH EAST CORNER

\*\*\*\*\*/

```
#include<stdio.h>
#include<conio.h>
void main()
{
    int sn,dn,i,j,ss=0,ds=0,sum=0;
    int sup[10],dem[10];
    int a[10][10],c[10][10];
    clrscr();
    //getting no.of supply & demand.
    printf("Enter the num of supply:");
    scanf("%d",&sn);
    printf("Enter the num of demand:");
    scanf("%d",&dn);
    //clearing values in array.
    for(i=0,j=0;i<10,j<10;i++,j++)
```

```
{
    sup[i]=0;
    dem[j]=0;
}
//input supply values & calculate sum of supply.
for(i=0;i<sn;i++)
{
    printf("\n Enter supply value sup[%d]:",i);
    scanf("%d",&sup[i]);
    ss=ss+sup[i];
}
//input demand values & calculate sum of demand.
for(j=0;j<dn;j++)
{
    printf("\n Enter demand value dem[%d]:",j);
    scanf("%d",&dem[j]);
    ds=ds+dem[j];
}
if(ss!=ds)
{
    printf("\n unbalanced problem..");
    getch();
    exit(0);
}
//input transportation cost.
printf("\n Enter array values:");
for(i=0;i<sn;i++)
{
    for(j=0;j<dn;j++)
    {
        scanf("%d",&a[i][j]);
    }
}
//clearing cost array.
for(i=0;i<10;i++)
{
    for(j=0;j<10;j++)
    {
        c[i][j]=0;
    }
}
//calculation.
for(i=0,j=dn-1;i<sn,j>=0;)
{
    if(i==sn||j==-1)
        goto L1;
    if(dem[j]==sup[i]) //Checking demand=supply
    {
        c[i][j]=dem[j]*a[i][j];
        printf("\n c[%d][%d]=%d and sup=%d",i,j,c[i][j],sup[i]);
        j--;
        i++;
    }
    else if(dem[j]<sup[i]) //checking demand< supply
    {
        c[i][j]=dem[j]*a[i][j];
        sup[i]=sup[i]-dem[j];
        printf("\n c[%d][%d]=%d and sup=%d",i,j,c[i][j],sup[i]);
        dem[j]=0;
        j--;
    }
    else //demand >= supply
    {

```

```
        c[i][j]=sup[i]*a[i][j];
        dem[j]=dem[j]-sup[i];
        printf("\n c[%d][%d]=%d and dem=%d",i,j,c[i][j],dem[j]);
        i++;
    }
}
L1:
for(i=0;i<sn;i++)
    for(j=0;j<dn;j++)
        sum=sum+c[i][j];
printf("\n\n sum of transportation cost = %d",sum);
getch();
}
```

### **OUTPUT:**

Enter the num of supply: 3

Enter the num of demand:5

Enter supply value sup [0]:160

Enter supply value sup [1]:150

Enter supply value sup [2]:190

Enter demand value dem [0]:80

Enter demand value dem [1]:90

Enter demand value dem [2]:110

Enter demand value dem [3]:160

Enter demand value dem [4]:60

Enter array values: 42 48 38 37 0

40 49 52 51 0

39 38 40 43 0

c[0][4]=0 and sup=100

c[0][3]=3700 and dem=60

c[1][3]=3060 and sup=90

c[1][2]=4680 and dem=20

c[2][2]=800 and sup=170

c[2][1]=3420 and sup=80

c[2][0]=3120 and sup=80

sum of transportation cost = 18780

### **CONCLUSION**

The optimal solution obtained in this present investigation shows much more closeness with initial basic feasible solution obtained by South east corner rule. The comparison of optimal solution have been made with other methods of finding initial solutions and observe that South east corner method give the better initial feasible solutions which are closer to optimal solution. The objected oriented programs using c++ have been developed. This shows that the computed results tally with the results obtained c++ programming. Object oriented program code for said programs is given for better understanding.

## REFERENCES

1. Reeb, J.E. and S.A., Leaven good, "Transportation problem: a special case for linear programming problems", EM8779. Corvallis: Oregon State University Extension Service, pp. 1-35, 2002.
2. Charnes, A. and W.W. Cooper, "The stepping stone method of explaining linear programming calculations in transportation problems", *Management Science*, **1**(1): pp. 49-69, 1954.
3. Dantzig, G.B., "Linear Programming and extensions", Princeton, NJ: Princeton University press, 1963.
4. Taha Hamdy A., "Operation Research: An introduction", Prentice-Hall of India, 8<sup>th</sup> edition. 2006.
5. Reinfeld, N.V and Vogel, W.R., "Mathematical Programming", Englewood Cliffs, New Jersey: prentice-Hall, pp. 59-70, 1958.
6. Nabendu Sen *et al.*, "A study of transportation problem for an essential item of southern part of north eastern region of India as an OR model and use of object oriented programming", *International Journal of Computer Science and Network Security*, **10**(4), pp. 78-86, 2010.
7. Saleem, Z.R. and Imad, Z.R., "Hybrid two-stage algorithm for solving transportation problem", *Modern Applied Science*, **6**(4), pp. 12-22, 2012.
8. R. Palaniyappa and V. Vinoba, "A new type of transportation problem using object oriented model", *International Journal of Mathematical Archive-4*(11), 2013, 71-77.

**Source of Support: Nil, Conflict of interest: None Declared**